

Model	Voltage	Frequency	Rated Current	Rated Power	Max Air Flow**	Static Pressure	Fan Noise	Rated Temp. Range	Approvals
	(V)	(Hz)	(A)	(W)	(m ³ /h)	(Pa)	[db(A)]	(°C)	
FPF20KG*115BE-120	115 V a.c.	50/60	0.96/1.3	107/143	660/745	220/222	74.7/78.9	-10 ÷ +55	CE
FPF20KG*115BER-120	115 V a.c.	50/60	0.96/1.3	107/143	660/745	220/222	74.7/78.9	-10 ÷ +55	CE
FPF20KG*230BE-120	230 V a.c.	50/60	0.50/0.72	111/140	660/745	220/222	72.8/75.8	-10 ÷ +55	CE
FPF20KG*230BER-120	230 V a.c.	50/60	0.50/0.72	111/140	660/745	220/222	72.8/75.8	-10 ÷ +55	CE
FPF20KGR400TBER-120	400 V a.c.	50/60	0.180/0.200	93/123	660/745	220/222	76.0/79.0	-10 ÷ +55	CE

* U = RAL 7035 R = RAL 7032 N = RAL 9005 ** data with uncertainty of 15%

All specifications, data and drawing are subject to change without notice and are approximate.
Please refer to our terms of sales including our warranty and limited liabilities clauses.