



ELECTRICAL DATA

| Model | Motor | Supply | Full load | Start | Box Pedestal & Fan | Metal Pedestal & Fan |
|---------------|----------------|----------|-----------|-------|--------------------|----------------------|
| | | | | | Weight (Kg) | Weight (Kg) |
| | | | | | 3 Phase Only | |
| S35/6 | 2.2kW-930/min | 400/3/50 | 5.3A | 24A | 60 | 55 |
| S35/4L | 4.kW-1450/min | 400/3/50 | 11.4A | 75A | 65 | 65 |
| S35/4M | 5.5kW-1450/min | 400/3/50 | 11.4A | 75A | 65 | 65 |
| S35/4H | 7.5kW-1450/min | 400/3/50 | 14.7A | 96A | 102 | 80 |

Maximum airflow temperature: 50°C

SOUND DATA

| /min | dB(A) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | Hz |
|-------------------|-----------|----|-----|-----|-----|------|------|------|------|-------|
| 930 - 2.2kW | 75 | 71 | 81 | 83 | 86 | 85 | 85 | 83 | 74 | dB(A) |
| 1450 - 4kW, 5.5kW | 79 | 75 | 85 | 87 | 90 | 89 | 89 | 87 | 78 | dB(A) |

Sound Power (Lw) in dB(A)

Sound Pressure at 3m range in dB(A)